imagePROGRAF iPF770 MFP L36

An affordable, space saving large-format MFP designed for easy operation

The iPF770 MFP L36 solution is a user-friendly, affordable and lightweight large-format workflow system, which makes it simple to scan and copy featuring a small footprint that takes up minimal space.







Key features:

- Simple scan-to-copy solution
- Scan direct to USB stick or to a network via a PC using the Ethernet connection
- User-friendly interface with quick and easy navigation
- Compact 36" design with lightweight scanner takes up minimal space and enables easy set up
- SingleSensor with multiple LED illumination for excellent line definition and accuracy
- Up to 3.0 inches per second scanning; 600 dpi optical resolution
- Scan to TIFF, PDF and JPEG up to 2.27 m in length

IPF770 MFP L36 36 INCH

COMPACT 36" DESIGN

LIGHTWEIGHT SCANNER

SIMPLE SCAN-TO-COPY

SCAN DIRECT TO USB STICK

5 COLOUR WITH NEW MAGENTA

> 2,400 X 1,200 DPI

130 ML INK TANKS



imagePROGRAF iPF770 MFP L36

Technical Specifications

SCANNER

Technology Scan speed

Scan to USB - RGB, Greyscale/BW, TIFF Scan to Network PC - RGB, Greyscale/BW, TIFF, JPEG, PDF, TIFF-G4 Copy - RGB, Greyscale/BW

Scan Accuracy

Resolution Maximum: 600 dpi, Optical: 600 dpi

Maximum Image Width Maximum Media Width Maximum scan length Maximum & Minimum Media Thickness

Control Panel User Interface

Scanner Interface

Scan to USB Scan to Network PC - L Scan

Included Software

Physical Dimensions -(W x D x H) and Weight (Kg) **External Power Supply**

Operating Environments

Scanner Power Consumption

Enviroment Certificates

What's In The Box?

SingleSensor with multiple LED illumination

COPY (scan / print) 300 / 300 dpi Draft = 1 inch/sec colour, 3 inches/sec mono 300 / 600 dpi Standard = 1inch/sec colour, 3 inches/sec mono 600 / 600 dpi Best = 0.5 inches/sec colour, 1.5 inches/sec mono

SCAN 200 dpi Draft = 1 inch/sec colour, 3 inches/sec mono 400 dpi Standard = 0.5 inches/sec colour, 1.5 inches/sec mono 600 dpi Best = 0.33 inches/sec colour, 1 inch/sec mono

0.2% +/-1 pixel

36" / 914.4 mm 38" / 965 2 mm 109" / 2768 mm Min = 0.07 mm Max = 0.5 mm

3" display (non touch). Home, Left, OK, Right, Start, Stop, Back,

Paper Eject buttons. Status LED

Ethernet 10 / 100 / 1000 Base-T / TX

USB2, 128GB FAT32.

Sets scan directory and file type. OS compatibility: Windows 7 / 8. x (32 / 64bit)

L Scan App software Languages : English, French, German, Italian, Spanish, Russian, Portuguese, Czech, Polish

Temperature: 10-35 °C Humidity: 10-90 % Standby (sleep): 0.05W Idle: 10.20W Scanning: 19.40W

• L scanner

Printer mounting brackets, fixings & 3mm tool
Document return guides
Calibration target

PRINTER

Printer Type Print Technology

Number of Nozzles

Print Resolution

Nozzle Pitch

Guaranteed Minimum Line Width

Line Accuracy Ink Droplet Size

Ink Capacity

Ink Type

Printer OS Compatability

Printer Languages

Standard Interfaces

Standard Memory

Media Thickness

Media Width

Scanner: 1238 (W) mm x 146 (D) mm x 131 (H) mm, Weight: 6.88 kg without Doc return guide, Paper Tray folded

Input: 100 - 240V, 50-60Hz Output: 3.42A at 19V

Europe: CE mark, Russia: EAC, Other Countries: CB Certification,

CD for L Scan App software (includes PDF documentation:
 L Scanner Guide and L Icon Guide per language)
 L Scanner Guide (includes Assembly Guide, User Guide & Outle State Guide)

Quick Start Guide).

Scale factor stickers
Ethernet cable
Power Supply Regional - Mains power cord(s)

5 Colour - 36" / 914.4 mm

Canon Bubblejet on Demand 6 colours integrated type (6 chips per print head $x\ 1$ print head)

Total: 15,360 MBK: 5,120 nozzles C, M, Y, BK: 2,560 nozzles each colour

2400 dpi x 1200 dpi

 $1200\ dpi \times 2$ includes Non-firing nozzle detection and compensation system

0.02 mm

±0.1 % or less

4 Picoliter per colour

Bundled Starter Ink: C, M, Y, Bk, MBk 90ml Sales Ink: C, M, Y, Bk, MBK 130ml

Dye/Pigment Reactive Ink: Cyan, Magenta, Yellow, Black Pigmen ink: 2 x Matte Black

Windows 32 bit – XP, Vista, 7, 8, 8.1 & 10 $\,$ Server 2003 / 2003R2, Server 2008

Server 2008 Windows 64 bit - Vista, 7, 8, 8.1 & 10 Server 2003 / 2003R2, Server 2008 / 2008R2, Server 2012 / 2012R2 Mac: OSX - 10.6.8 - 10.10.x

GARO (Graphic Arts language with Raster Operations), HP-GL/2, HP RTL

USB 2.0 High-Speed IEEE 802.3 10base-T IEEE 802.3 10base-TX / Auto-Negotiation IEEE 802.3ab 1000base-T / Auto-Negotiation IEEE 802.3ar Full Duplex IEEE 802.3az EEE

256MB

Roll paper: 10" / 254 mm - 36" / 914.4 mm Cut sheet: 8" / 203.2 mm - 36" / 914.4 mm

Roll Unit: 0.07 mm - 0.8 mm Top Loading Manual Feed: 0.07 mm - 0.8 mm

Roll: 18m (varies according to the OS and application) Cut Sheet: 1.6m

NOTES & RECOMMENDATIONS

Maximum Printable Length

Note 1 Tightly curled documets should be flattened as best as possible and the user should guide the document while it feeds through the scanner to prevent the original re-entering the

Note 2 SCAN to USB & COPY mode scan to internal memory first, then send data to the USB memory stick or the printer. Scan time to USB memory stick will varying depending with individual USB memory sticks.

Note 3 SCAN to Network PC - scans directly to the network, so the PC should be of a suitable specification to handle the large amounts of data from large format scans.

Note 4 Only 1 copy of the L Scan App should be running on the network subnet with the scanner. It is not possible to select the PC from the scanner.

Note 5 Only 1 supported printers should be on the network subnet with the scanner. It is not possible to select the printer from the scanner.

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and ®: All company and/ or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended











